

**TECHNICAL SUPPORT**

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

**PART NUMBERS**

81143 EPC-14 14 oz  
81145 EP-14 14 oz  
81178 EP-42B 42 lbs.

**TURNKEY SOLUTIONS**

As an ISO 9001:2015 certified company, SAF-T-LOK can design or refine products to fit your company's specific needs and requirements.

For more information on any of our products or services please visit us on the Web at: [www.saftlok.com](http://www.saftlok.com)

**GENERAL INFORMATION:**

**SAF-T-EZE Extreme Pressure Bearing Lubricant** is multi-purpose high performance lithium soap thickened grease that exhibits superior high temperature stability to as high as 360°F for intermittent use. This grease has been compounded for high as well as low speed bearings and provides higher service performance than conventional greases. **SAF-T-EZE Extreme Pressure Bearing Lubricant** includes additives to resist extreme pressures and contains corrosion inhibitors to prevent rust promotion.

**PHYSICAL PROPERTIES:**

<b>Color:</b>	<b>Amber</b>	
NGLI:	2	
<b>Drop Point:</b>	<b>360°F</b>	<b>ASTM 2265</b>
Thickener Type:	Lithium	
<b>Base Oil Properties</b>		
cSt @ 100°C	13.8 – 18.7	ASTM D 445
Viscosity Index (Min.)	50	ASTM D 2270
Penetration @ 77°F		
Worked:	285	ASTM D 217
<b>Wheel Bearing Test:</b>		
260°F, 130 gm, r Hr.	20gm, Max	ASTM D 1263
Water Washout:	Nil	
<b>Rust Protection:</b>	<b>Pass</b>	
Texture:	Smooth	

**NOTE: This product is not recommended for use on pure oxygen systems.**

**IMPORTANT NOTICE:** All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.