

Contact-Clean

Technical Data Sheet

GENERAL INFORMATION: *SAF-T-EZE Contact-Clean* is designed to remove oxidation, carbon, grease, oil, dirt and corrosion deposits on equipment,. This special solvent leaves a clean, dry surface. *SAF-T-EZE Contact-Clean* is fast drying, non-staining, non-conductive, and leaves no film or residue. This product meets ASTM D 6368. Physical properties and performance equal to 1,1,1. trichloroethane. It is a flammable product, however.

PHYSICAL PROPERTIES:

Flash Point	None
Boiling Point	70°C/160°F
Specific Gravity @ 25°C	1.33 gm/cc
Evaporation Rate	4.5

APPLICATIONS:

- Flushes dirt and oil away
- Cleans without rinsing
- No flash point
- Eliminates noise caused by dust and dirt

DIRECTIONS: For best results, spray at room temperature (70°F). Shake the can well before using. Spray liberally on items to be cleaned and allow dirt to flush off and solvent to evaporate.

COMPATABILITY:

- METALS - Aluminum, Bronze, Copper, Cast Iron, Carbon Steel, Hastaloy (A,B,C), Cromium, Lead, Magnesium, Naval Brass, Nickel, Platinum, Silver, 316 Stainless Steel Tin, Zinc
- PLASTICS - PVC , Polyethylene, Polypropylene, Polyurethane, Delrin, Furane Resin, Epoxy Resin, PTFE, Nylon
- ELASTOMERS - Acrylonitrile-Butadiene, Butadiene Nitrile, Butadiene Styrene, Chloroprene, Fluoroelastomers (Viton A, B), Polysulfide, Butyl, Polysiloxane etc.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. SAF-T-EZE Div., SAF-T-LOK International Corporation is not responsible for loss, claim or damages resulting from use of its products.