

#### TECHNICAL SUPPORT

Our technical support team stands ready to assist you with your technical questions regarding your SAF-T-LOK products. On-Site support when necessary within 24 hours.

#### PART NUMBERS

80102	1gm
80112	1oz
80122	4oz
80127	4oz
80137	8oz
80153	16oz
80155	16oz
80156	12oz
80157	16oz
80158	500gm
80160	2.5lb
50161	1k
80165	8 lb
80178	42lb
80189	130lb
80199	425lb

#### SPECIFICATIONS

MIL-PRF-907E

#### TURNKEY SOLUTIONS

As an ISO 9001:2015 certified company, SAF-T-LOK can design or refine products to fit your company's specific needs and requirements.

For more information on any of our products or services please visit us on the Web at:  
[www.saftlok.com](http://www.saftlok.com)

## PRODUCT DESCRIPTION:

**SAF-T-EZE Regular High-Temp Anti-seize** is a smooth non-separating formula consisting of lithium soap thickened grease into which is compounded very fine flaked copper, as well as graphite lubricants and corrosion fighting inhibitors. The high performance grease and solid additives provide extreme pressure lubricating properties that prevent galling and cold welding and at the same time prevents water wash out and galvanic pitting from electrolysis of road salt, acid rain, or salt water. **SAF-T-EZE Regular High-Temp Anti-Seize** is non-hardening and has exceptional thermal stability. The particles present are inert and will not evaporate at extreme temperatures, and their heat resistant qualities will prevent carbon fusion and seizure at temperatures up to 2000°F. This anti-seize compound does not contain lead, molybdenum disulfide or halogen compounds.

## GENERAL INFORMATION:

**SAF-T-EZE Regular Grade** provides protection as a high temperature anti-seize and extreme pressure lubricant. **SAF-T-EZE** stops corrosion galling and seizing between metal parts. **Regular High-Temp** performs to 2000°F.

## PHYSICAL PROPERTIES:

<b>Color</b>	<b>Silver Grey</b>
Temperature Range	-65°F to 2000°F
<b>NLGI</b>	<b>3</b>
Specific Gravity	1.28
<b>Weight per Gallon</b>	<b>10.68 lb</b>
Penetration Range	225 ± 25
<b>Drop Point</b>	<b>350°F</b>
Flash Point C.O.C.	302°F (CC)
<b>Particle Size</b>	<b>1 Mil Maximum (25)</b>
"K" Value	0.16
<b>Timken OK Load</b>	<b>47 lbs. (ASTM D2509)</b>
Timken Fail Load	52 lbs. (ASTM D2509)

## APPLICATION:

**SAF-T-EZE Regular Anti-Seize** can be used as a lubricant, a sealer, a break in lubricant, or tapping compound on plastics as well as metals. Surfaces are best cleaned before application as grit or low quality oil/grease may be present and best performance is required. The reduction in assembly friction increases torque tension by about 20 percent. Use on threaded parts, bushings, gears, valve stems, chains, sprockets, levers, hinges, pivots, rollers, heat exchanger or manifold bolts, or as a gasket release agent, etc.

NOTE: This product is not recommended for use with pure oxygen systems.

**IMPORTANT NOTICE:** All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-LOK International Corporation** is not responsible for loss, claim or damages resulting from use of its products.